

Indoor Modular Silos

Tunetanken Indoor Modular Silos provide an optimal storage and discharge solution, that is specially suited for customers' needs. Indoor Modular Silos are of the highest quality and are developed to ensure the best conditions for filling, storage and efficient emptying, as well as have a long life cycle.

All structural components of Tunetanken Indoor Modular Silos are produced in fiber-reinforced composite material, which, along with a unique design and our great expertise, assures hygienic storage, well functioning operating conditions as well as optimal service.

Comes with

- > Fully moulded construction elements.
- > Inlet at the top measuring \varnothing 500 mm.
- > Inspection hatch.
- > Cone with a 60° slope.
- > Outlet measuring 300 mm x 300 mm.



Illustration	Type	Volume		Dimensions			
		Volume	Content ¹	Width (A)	Length	Total Height (B)	Free Height (C)
	IC 6	6 m ³	3,9 t	3,000	3,000	2,911	538
	IC 11	11 m ³	7,2 t	3,000	3,000	3,551	538
	IC 16	16 m ³	10,4 t	3,000	3,000	4,191	538
	IC 21	21 m ³	13,7 t	3,000	3,000	4,831	538
	IC 26	26 m ³	16,9 t	3,000	3,000	5,471	538
	IC 31	31 m ³	20,2 t	3,000	3,000	6,111	538
	IC 36	36 m ³	23,4 t	3,000	3,000	6,751	538
	IC 41	41 m ³	26,7 t	3,000	3,000	7,391	538
	IC 46	46 m ³	29,9 t	3,000	3,000	8,031	538
	IC 51	51 m ³	33,2 t	3,000	3,000	8,671	538
	IC 56	56 m ³	36,4 t	3,000	3,000	9,311	538
	IC 61	61 m ³	39,7 t	3,000	3,000	9,951	538
	IC 66	66 m ³	42,9 t	3,000	3,000	10,591	538

*All undefined measurements are in mm.

¹ Approx. amount of fodder in a ton with a density of 650 kg/m³